

# | TECHNICAL FEATURES | CARATTERISTICHE TECNICHE





## TECHNICAL SPECIFICATIONS FOR EXTRUDED CERAMIC TILES

CONFORMING TO EN 14411 ISO 13006 STANDARDS ANNEX F GROUP AIII GL EB > 10%

CARATTERISTICHE TECNICHE CERAMICA ESTRUSA Conformi a norme EN 14411 ISO 13006 Appendice F Gruppo AIII GL EB > 10%

TECHNISCHE EIGENSCHAFTEN STRANGEZOGENEN FLIESEN Gemäß den Normen EN 14411 ISO 13006 Appendix F Gruppe AIII GL EB > 10%

CARACTÉRISTIQUES TECHNIQUES POUR CARREAUX CÉRAMIQUES EXTRUDÉES Conformes aux normes EN 14411 ISO 13006 Appendice F Groupe AIII GL EB > 10%

	TECHNICAL FEATURES CARATTERISTICHE TECNICHE TECHNISCHE DATEN CARACTÉRISTIQUES TECHNIQUES	TESTING METHOD METODICA DI PROVA PRÜFVERFAHREN NORME D'ESSAIS	TEST RESULTS VALORE PRODOTTO PRODUKT WERTE VALEUR PRODUIT
	Water absorption Assorbimento d'acqua Wasseraufnahme Absorption d'eau	EN ISO 10545-3	E <sub>b</sub> >10%
	Breaking strength Carico di rottura Bruchlast Charge de rupture	UNI EN ISO 10545-4	> 600 N
	Glaze crazing resistance Determinazione della resistenza al cavillo Glaserhaarrißbeständigkeit Résistance aux taches	UNI EN ISO 10545-11	Resistant Resistente Widerstandsfähig Résistant
	Chemical resistance Resistenza ai prodotti chimici Chemikalienbeständigkeit Résistance aux produits chimiques	UNI EN ISO 10545-14 UNI EN ISO 10545-13	Min. class 3 Min. class B



V2 MODERATE

## DECLARATION OF PERFORMANCE

N°14-002-WALL TERRATINTAGROUP SRL

1. Unique identification code of the product type:

Type, batch or serial number or any other element allowing identification of the product

**DRY PRESSED CERAMIC TILE, WITH WATER ABSORPTION Eb >10%**

2. Intended use(s):

**FOR INTERNAL WALLS**

3. Name registered trade mark and contact address of the manufacturer

**Terratinta Group Srl**  
Via Monte bianco 55, 41042 Fiorano Modenese (MO) - Italy  
VAT IT03197969366 - [info@terratintagroup.com](mailto:info@terratintagroup.com)

4. System(s) of assessment and verification of constancy of performance (AVCP)

**System 4**

5. Name and identification number of notified laboratory if relevant : N.A

Task(s) carried out : N.A.

AVCP system N.A

Document issued and date of issue : N.A

6. Declared performances:

Essential characteristics	Performance	Technical specification
Reaction to fire	A1	EN 14411:2016
Realease of dangerous substances for:		
Cadmium	NPD	
Lead	NPD	
Breaking Strenght	> 600 N	
Bond Strenght/Adhesion for: Cementitious adhesive, type C1	>= 0.5 N/mm2	
Durability for:		
Internal use	pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by

Alessandro Carnovali  
Quality Manager - Terratinta Group Srl



Fiorano Modenese; 04/11/19

This declaration of performance is not applicable to decorative accessories and special trims




**SARTORIA** \* est. 2018

**Terratinta Group srl**

Via Monte Bianco 55, 41042 Fiorano Modenese (MO) Italy | T +39 0536911408 | F +3905361940223  
W [www.terratintagroup.com](http://www.terratintagroup.com) | E [info@terratintagroup.com](mailto:info@terratintagroup.com) | VAT IT03197960366

## CE MARKING


<p><i>Terratinta group srl</i> <i>Via Monte bianco 55, 41042 Fiorano Modenese</i> <i>(MO) - Italy</i></p> <p>N°14-002- WALL TERRATINTAGROUP SRL</p>
<p>EN14411:2016</p> <p>Dry pressed ceramic tile, with water absorption <math>E_b &gt; 10\%</math> for internal walls.</p>